



NOTE

- DO NOT R-MP BULLNOSE -T SIGN-LIZED END OF ISL-ND
- H-NDHOLE S-400.032 LOC-TION, 2m LESS TH-N ISL-ND LENGTH, IF ISL-ND IS LESS TH-N 17m.
- CONTR-CTION JOINTS TO BE LOC-TED -T M-XIMUM INTERV-LS OF 1.5m OC. JOINTS TO BE S- CUT TO - DEPTH OF 50mm.
- CONTR-CTION JOINTS (5mm X 50mm) -RE TO BE CUT IN THE CONCRETE SL-B PERPENDICUL-R TO THE CURB -T THE MID-POINT OF THE POLES OR PULL BOXES.
- EXP-NSION JOINTS TO BE 12mm BITUMINOUS FIBRE BO-RD SET -T 12mm BELOW GR-DE -ND FINISHED WITH CONCRETE COLOUR M-TCHED POLYSULPHITE SE-L-NT FLUSH WITH FINISHED GR-DE LOC-TE EXP-NSION JOINT EVERY THIRD JOINT -ND WHERE CONCRETE SURF-CE MEETS OTHER H-RD SURF-CES -ND STRUCTURES.
- SURF-CE TRE-TMENT TO BE BROOM FINISHED -ND NO COLOUR UNLESS OTHERWISE SPECIFIED.

-LL DIMENSIONS IN METRES EXCEPT WHERE NOTED.



WORKS DEP-RTMENT

TRAFFIC SIGNAL AND ISLAND DETAIL (CONCRETE PAD/INTERLOCKING PAVERS)

DWG. D-TE: 2002 10

REVISION NO.: 12

REV. D-TE: 2024 12

SC-LE: N.T.S.

S-300.070