



NOTES:

1. ALL METAL TRAFFIC SIGNAL HARDWARE TO BE BONDED TO SERVICE GROUND.
2. ON CONCRETE POLES, MOUNT CONDUITS USING 16 mm STAINLESS STEEL STRAPPING AND BUCKLES. ON WOOD POLES, MOUNT CONDUITS USING GALVANIZED PIPE STRAPS WITH 6 X 38 mm LAG SCREWS. MAXIMUM STRAPPING SPACING - 1200 mm.
3. FOR ORIENTATION AND LOCATION OF POLES AND EQUIPMENT REFER TO LAYOUT DRAWINGS.
4. WHERE UNDERGROUND RACEWAYS OR CABLES ARE SUBJECT TO MOVEMENT BY SETTLEMENT OR FROST, PROVISION SHALL BE MADE SO AS TO PREVENT DAMAGE TO THE CONDUCTORS OR THE ELECTRICAL EQUIPMENT.

ALL DIMENSIONS IN MILLIMETRES EXCEPT WHERE NOTED.



WORKS DEPARTMENT

**TRAFFIC SIGNAL EQUIPMENT INSTALLATION
ON WOOD OR CONCRETE POLE
(UNDERGROUND WIRING)**

DWG. DATE: 2008 04
REVISION NO.: 4
REV. DATE: 2023 04
SCALE: N.T.S.

S-410.022